# Technical Data Sheet

## ATP Mount

## Product: GM- 107 Q

### Product Description:

Quality Laminate
For the permanent, self-adhesive lamination of even surfaces. Very well processible, provides excellent adhesion to almost all materials like plastics, films, wood, glasses or metals with excellent flatness. Suitable for in- and outdoor application.

### Product structure:

| | |
|---|---|
| **Support** | PET film, 12 µm, transparent |
| **Interliner** | Release paper, special coating, white, 90 g/m² |
| **Adhesive** | pure polyacrylic , permanent, transparent, |
| **Total Thickness** | 0,07 mm |
| **Adhesive weight** | 60 g/m² |

### Characteristics:

| | | Average Value | Test Method |
|---|---|---|---|
| **Adhesion on steel:** | (after 20 min.) | 8 N / 25mm | AFERA 5001 |
| **Adhesion on steel:** | (after 24 h) | 11 N / 25mm | AFERA 5001 |

**ATP adhesive systems AG**
Sales International, R&D
Sihleggstr. 23, Postfach 127
CH - 8832 Wollerau
Telefon: +41(0)43/888-1515
Telefax: +41(0)43/888-1510
Email: info@atp-ag.ch

More Information can be found on:
www.atp-ag.com

22.02.2012

**ATP adhesive systems GmbH**
Vertrieb Deutschland
Eichenhofer Weg 71
D - 42279 Wuppertal
Telefon: +49(0)2339/909-750
Telefax: +49(0)2339/909-506
Email: info@atp-ag.com

| | |
|---|---|
| **Application temperature:** | min. 10°C |
| **End-Use Temperature range:** | from -40°C to +150°C |
| **Shelf life:** | 2 years (see application information) |
| **Durability:** | 2 years |

The estimated durability is based on accelerated ageing tests and refers to a vertical exposure under middle European climates. The durability of the product depends on the substrate's preparation, the atmospheric conditions and the environmental influence. Exposure to extreme conditions (tropical climate, high humidity, high UV-light exposure or polluted areas) can decrease the durability in a dramatically way.

All our products are subjected to a strict quality control by our QM-System, which is in accordance with ISO/TS 16949, DIN EN ISO 9001 and DIN EN ISO 14001. The information is based on our present knowledge and our experience. Because of the large number of of possible influences during the processing and application of our products, this information does not release the user from the obligation to conduct his own tests and trials. Users of our products are responsible for observing any patent rights that may exist and for following existing regulations. Our applications technology section is always pleased to give advice about suitability tests on original materials.

**ATP adhesive systems AG**
Sales International, R&D
Sihleggstr. 23, Postfach 127
CH - 8832 Wollerau
Telefon: +41(0)43/888-1515
Telefax: +41(0)43/888-1510
Email: info@atp-ag.ch



**ATP adhesive systems GmbH**
Vertrieb Deutschland
Eichenhofer Weg 71
D - 42279 Wuppertal
Telefon: +49(0)2339/909-750
Telefax: +49(0)2339/909-506
Email: info@atp-ag.com