

## APLITAPE 4075

### HEAVYWEIGHT PAPER APPLICATION TAPE

## TECH DATA SHEET

4075 is standard weight saturated paper coated with a high tack rubber adhesive designed specifically as a premasking of small and mid-sized die cut or prespaced vinyl and printed graphics.

#### PHYSICAL SPECIFICATIONS

<b>Adhesive</b>	Rubber-based
<b>Color</b>	White/Translucent
<b>Caliper</b> <i>facestock</i>	100-113 microns (4.0 -4.5 mils)
<b>Caliper</b> <i>facestock + adhesive</i>	125-138 microns (5.0 - 5.5 mils)
<b>Adhesion to Steel*</b>	18 - 20 N/100mm (16 - 18 oz.)
<b>Tensile</b>	297 N/100mm (17lb./in)
<b>Elongation</b>	3-4%
<b>Tear Resistance</b>	50
<b>Shelf Life**</b>	1 year
<b>Base</b>	{tag_base}

#### APPLICATIONS

- Premask for small and medium size vinyl graphics.
- All-purpose application tape for wet and dry applications.
- Excellent for transferring graphics to banners.

#### PRINTER PROFILES

Printer profiles are available on [rtape.com](http://rtape.com).

#### WARRANTY

Tapes are only warranted to be free of defect in workmanship or materials at time of shipment. Manufacturer will replace or credit any material manufacturer deems defective. No acceptance or responsibility for loss, damage, or expense, implies or otherwise, shall be assumed by seller or manufacturer. User assumes all risk and liability herewith.

#### FEATURES

- Removes easily following graphics application.
- If adhesive touches adhesive, Conform pulls apart easily with no adhesive delamination.
- Works well in either wet or dry applications with no adhesive transfer.

\* Adhesion PSTC-101, 1 min dwell on stainless steel

\*\* Stored at 22 0C / 50-55% RH



**RTape Corp.**  
6 Ingersoll Road  
South Plainfield, NJ  
07080  
T 1-800-440-1250  
[www.rtape.com](http://www.rtape.com)

RESPONSIVE  
RELIABLE  
RESOURCEFUL